SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 22-Oct-2025 **Version** 1

1. Identification

Product identifier

Product Name Wynn's #5 FOAM SPRAY The Nut Buster

Other means of identification

Product Code WN 55550

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Restrictions on use All other applications

Details of the supplier of the safety data sheet

Supplier Address
ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803

Manufacturer Address

Manufactured and Distributed by:

Distributor

May Also Be Distributed by:
Logistic Distribution
550 Industrial Drive
Milton, ON, Canada L9T 5A6

Emergency telephone number

Company Phone Number 863-665-3338

24-hour emergency phone number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003583

2. Hazard(s) identification

Classification of the substance or mixture

Aerosols	Category 1
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Carcinogenicity	Category 1B
Aspiration hazard	Category 1

Label elements

Danger

Hazard statements
Extremely flammable aerosol. Pressurized container: May burst if heated.
Harmful if inhaled.
May cause cancer.
May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection and face protection.
Avoid breathing dust, fume, gas, mist, vapors and spray.
Use only outdoors or in a well-ventilated area.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.
Do not spray on an open flame or other ignition source.
Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention.
Inhalation
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor if you feel unwell.
Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Do NOT induce vomiting.

Precautionary Statements - Storage
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Precautionary Statements - Disposal
Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Unknown acute toxicity
14 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
45 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
86 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
78 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Hazards classified under paragraph (d)(1)(ii) of 1910.1200
No information available.

Other Information
May be harmful if swallowed. May be harmful in contact with skin. Causes mild skin irritation. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	**Hazardous Material Information Review Act registry number (HMIRA registry #)**	**Date HMIRA filed and date exemption granted (if applicable)**
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	10-30%	-	-
2-Methylnaphthalene	91-57-6	10-30%	-	-
Propane	74-98-6	10-30%	-	-
1-Methylnaphthalene	90-12-0	10-30%	-	-
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	5-10%	-	-
Distillates (petroleum), hydrotreated light	64742-47-8	5-10%	-	-
4-methylpentan-2-ol	108-11-2	3-7%	-	-
BUTANE	106-97-8	1-5%	-	-
2-Butoxyethanol	111-76-2	1-5%	-	-
Naphthalene	91-20-3	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Inhalation Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin contact Wash skin with soap and water.

Ingestion ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid breathing vapors or mists. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause redness and irritation.

Effects of Exposure May cause cancer.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical No information available.

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters
Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
2-Methylnaphthalene 91-57-6	TWA: 0.05 ppm SL: 3 mg/100 cm2	-	-

	pSk		
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard Sa	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	TWA: 1000 ppm; TWA: 1800 mg/m³; IDLH: 2100 ppm
1-Methylnaphthalene 90-12-0	TWA: 0.05 ppm SL: 3 mg/100 cm2 pSk	-	-
4-methylpentan-2-ol 108-11-2	TWA: 20 ppm STEL: 40 ppm	TWA: 25 ppm TWA: 100 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 100 mg/m³ (vacated) STEL: 40 ppm (vacated) STEL: 165 mg/m³ dSk Sdv	TWA: 25 ppm; TWA: 100 mg/m³; STEL: 40 ppm STEL: 165 mg/m³ IDLH: 400 ppm
BUTANE 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	TWA: 800 ppm; TWA: 1900 mg/m³; IDLH: 1600 ppm
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ dSk Sdv	TWA: 5 ppm; TWA: 24 mg/m³; IDLH: 700 ppm
Naphthalene 91-20-3	TWA: 10 ppm pSk	TWA: 10 ppm TWA: 50 mg/m³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m³	TWA: 10 ppm; TWA: 50 mg/m³; STEL: 15 ppm STEL: 75 mg/m³ IDLH: 250 ppm

Chemical name	Alberta	British Columbia	Ontario	Quebec
2-Methylnaphthalene 91-57-6	-	TWA: 0.5 ppm; Sk	TWA: 0.5 ppm; dSk	TWAEV: 0.5 ppm; Sd
Propane 74-98-6	TWA: 1000 ppm;	Sa	: ; Sa (See Appendix F: Minimal Oxygen Content;explosion hazard)	Sa
1-Methylnaphthalene 90-12-0	-	TWA: 0.5 ppm; Sk	TWA: 0.5 ppm; dSk	TWAEV: 0.5 ppm; Sd
4-methylpentan-2-ol 108-11-2	TWA: 25 ppm; TWA: 104 mg/m³; STEL: 40 ppm; STEL: 167 mg/m³; pSk	TWA: 20 ppm; STEL: 40 ppm;	TWA: 25 ppm; STEL: 40 ppm; dSk	TWAEV: 20 ppm; STEV: 40 ppm;
BUTANE 106-97-8	TWA: 1000 ppm;	STEL: 1000 ppm;	: ; STEL: 1000 ppm;	TWAEV: 800 ppm; TWAEV: 1900 mg/m³;
2-Butoxyethanol 111-76-2	TWA: 20 ppm; TWA: 97 mg/m³;	TWA: 20 ppm;	TWA: 20 ppm;	TWAEV: 20 ppm;
Naphthalene 91-20-3	TWA: 10 ppm; TWA: 52 mg/m³; STEL: 15 ppm; STEL: 79 mg/m³; pSk	TWA: 10 ppm; Sk	TWA: 10 ppm; dSk	TWAEV: 10 ppm; Sd

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
2-Methylnaphthalene	TWA: 0.05 ppm; SL: 3 mg/100 cm2; pSk	TWA: 0.5 ppm; pSk	TWA: 0.05 ppm; SL: 3 mg/100 cm2; pSk	TWA: 0.05 ppm; SL: 3 mg/100 cm2; pSk
Propane	: ; Sa (See Appendix F: Minimal Oxygen Content)	: ;	: ;	: ; Sa (See Appendix F: Minimal Oxygen Content)
1-Methylnaphthalene	TWA: 0.05 ppm; SL: 3 mg/100 cm2; pSk	TWA: 0.5 ppm; pSk	TWA: 0.05 ppm; SL: 3 mg/100 cm2; pSk	TWA: 0.05 ppm; SL: 3 mg/100 cm2; pSk
4-methylpentan-2-ol	TWA: 20 ppm; STEL: 40 ppm;	TWA: 25 ppm; STEL: 40 ppm; pSk	TWA: 20 ppm; STEL: 40 ppm;	TWA: 20 ppm; STEL: 40 ppm;
BUTANE	STEL: 1000 ppm;	STEL: 1000 ppm;	STEL: 1000 ppm;	STEL: 1000 ppm;
2-Butoxyethanol	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;
Naphthalene	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
2-Methylnaphthalene		TWA: 0.05 ppm; SL: 3 mg/100 cm2;		
Propane	TWA: 1000 ppm; STEL: 1250 ppm;	: ;	TWA: 1000 ppm; STEL: 1250 ppm;	Sa
1-Methylnaphthalene		TWA: 0.05 ppm; SL: 3 mg/100 cm2;		
4-methylpentan-2-ol	TWA: 25 ppm; STEL: 40 ppm; Sk	TWA: 20 ppm; STEL: 40 ppm;	TWA: 25 ppm; STEL: 40 ppm; pSd	TWA: 25 ppm; TWA: 100 mg/m³; STEL: 40 ppm; STEL: 150 mg/m³; Sk
BUTANE	TWA: 1000 ppm; STEL: 1250 ppm;	STEL: 1000 ppm;	TWA: 1000 ppm; STEL: 1250 ppm;	TWA: 600 ppm; TWA: 1400 mg/m³; STEL: 750 ppm; STEL: 1600 mg/m³;
2-Butoxyethanol	TWA: 20 ppm; STEL: 30 ppm;	TWA: 20 ppm;	TWA: 20 ppm; STEL: 30 ppm;	TWA: 50 ppm; TWA: 240 mg/m³; STEL: 150 ppm; STEL: 720 mg/m³; Sk
Naphthalene	TWA: 10 ppm; STEL: 15 ppm; Sk	TWA: 10 ppm;	TWA: 10 ppm; STEL: 15 ppm; pSd	TWA: 10 ppm; TWA: 50 mg/m³; STEL: 15 ppm; STEL: 75 mg/m³;

Biological occupational exposure limits

Chemical name	ACGIH
2-Butoxyethanol 111-76-2	200 mg/g creatinine - urine (Butoxyacetic acid with hydrolysis) - end of shift
Naphthalene 91-20-3	- (1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing.

Respiratory protection Use appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid
Physical state	Aerosol
Color	Yellow
Odor (includes odor threshold)	Solvent

Property	**Values**	**Remarks • Method**
Melting point / freezing point	No data available	
Boiling point (or initial boiling point or boiling range)	7 °C / 44.6 °F	
Flammability (solid, gas)	Flammable Aerosol	
Flammability Limit in Air		
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Flash point	70 °C / 158 °F	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
SADT (°C)	No data available	
pH	8.8	
pH (as aqueous solution)	No data available	
Kinematic viscosity	<14 mm2/s	
Dynamic viscosity	No data available	
Solubility	No Data Available	
Water solubility	Immiscible in water	
Partition coefficient n-octanol/water (log value)	No Data Available	
Vapor pressure (includes evaporation rate)	44-55	
Evaporation rate	Not applicable	
Density and/or relative density	0.834	
Bulk density	No data available	
Density	No data available	
Vapor density	Heavier than Air	
Particle characteristics		
Particle Size	No data available	
Particle Size Distribution	No data available	

Other information

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Excessive heat.

Incompatible materials None known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes mild skin irritation. May be harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause redness and irritation.

Acute toxicity Harmful by inhalation.

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	2,547.80 mg/kg
ATEmix (dermal)	2,919.90 mg/kg
ATEmix (inhalation-gas)	379,720.90 ppm
ATEmix (inhalation-vapor)	10.10 mg/l
ATEmix (inhalation-dust/mist)	1.94 mg/l

Unknown acute toxicity

14 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
45 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
86 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
78 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha (petroleum), heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 590 mg/m³ (Rat) 4 h
2-Methylnaphthalene 91-57-6	= 1630 mg/kg (Rat)	-	-
Propane 74-98-6	-	-	> 800000 ppm (Rat) 15 min
1-Methylnaphthalene 90-12-0	= 1840 mg/kg (Rat)	-	-
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Distillates (petroleum), hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
4-methylpentan-2-ol 108-11-2	= 2600 mg/kg (Rat)	= 2880 mg/kg (Rabbit)	> 16000 mg/m³ (Rat) 4 h
BUTANE 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Naphthalene 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 0.4 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
2-Methylnaphthalene 91-57-6	A4 - Not Classifiable as a Human Carcinogen	-	-	-
1-Methylnaphthalene 90-12-0	A4 - Not Classifiable as a Human Carcinogen	-	-	-
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5	A2 - Suspected Human Carcinogen	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present
2-Butoxyethanol 111-76-2	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 3 - Unclassifiable as to carcinogenicity in humans	-	-
Naphthalene 91-20-3	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	Reasonably Anticipated To Be A Human Carcinogen	Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Solvent naphtha (petroleum), heavy aromatic 64742-94-5	-	LC50: =19mg/L (96h, Pimephales promelas) LC50: =2.34mg/L (96h, Oncorhynchus mykiss) LC50: =1740mg/L (96h, Lepomis macrochirus) LC50: =45mg/L (96h, Pimephales promelas) LC50: =41mg/L (96h, Pimephales promelas)	-	EC50: =0.95mg/L (48h, Daphnia magna)
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
Distillates (petroleum), hydrotreated light 64742-47-8	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss)	-	-
4-methylpentan-2-ol 108-11-2	-	LC50: >92.4mg/L (96h, Pimephales promelas)	-	-
2-Butoxyethanol 111-76-2	-	LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	-	EC50: >1000mg/L (48h, Daphnia magna)
Naphthalene 91-20-3	-	LC50: 5.74 - 6.44mg/L (96h, Pimephales promelas) LC50: =1.6mg/L (96h, Oncorhynchus mykiss) LC50: 0.91 - 2.82mg/L (96h, Oncorhynchus mykiss) LC50: =1.99mg/L (96h, Pimephales promelas) LC50: =31.0265mg/L (96h, Lepomis macrochirus)	EC50 = 0.93 mg/L 30 min EC50 > 20 mg/L 18 h	LC50: =2.16mg/L (48h, Daphnia magna) EC50: =1.96mg/L (48h, Daphnia magna) EC50: 1.09 - 3.4mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Solvent naphtha (petroleum), heavy aromatic 64742-94-5	6.5
2-Methylnaphthalene 91-57-6	3.86
Propane 74-98-6	1.09
4-methylpentan-2-ol 108-11-2	1.43
BUTANE 106-97-8	2.31
2-Butoxyethanol 111-76-2	0.81
Naphthalene 91-20-3	3.4

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number U165

California waste information This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

NOTE: This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

UN number or ID number UN1950
Proper shipping name Aerosols, Flammable
Transport hazard class(es) 2.1

IATA

UN number or ID number UN1950
UN proper shipping name Aerosols, Flammable
Transport hazard class(es) 2.1

IMDG

UN number or ID number UN1950
UN proper shipping name Aerosols, Flammable

Transport hazard class(es) 2.1

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	1.0
Naphthalene - 91-20-3	0.1

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Naphthalene 91-20-3	100 lb / 1 lb / kg (final RQ) kg (final RQ)	-	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

NonHazardous

Chemical name	California Proposition 65
Naphthalene - 91-20-3	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
2-Methylnaphthalene 91-57-6	X	-	-
Propane 74-98-6	X	X	X
1-Methylnaphthalene 90-12-0	X	X	X
4-methylpentan-2-ol 108-11-2	X	X	X
2-Butoxyethanol 111-76-2	X	X	X
BUTANE 106-97-8	X	X	X
Naphthalene 91-20-3	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA **Health hazards** 3 **Flammability** 2 **Instability** 0 **Special hazards** -

HMIS **Health hazards** 3 * **Flammability** 2 **Physical hazards** 0 **Personal protection** X

Chronic Hazard Star Legend ** = Chronic Health Hazard*

Revision Date 22-Oct-2025

Revision Note No information available.

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled.

However,Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of theinformation. User is responsible for evaluating whether such information or this product is fit for a particular purposeand suitable for a particular use or application. The information in this data sheet may not be valid if this product is usedin combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims anyliability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of thisproduct. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.