



ZW21000 POWER DIESEL™ INDUCTION & EGR SERVICE TOOL JOB AID

Technical Support: 833-364-5932

Safety Recommendations:

- Safety glasses and gloves should be worn during the service.
- Keep loose clothing and/or tools secured while engine is running.
- Use in well ventilated area.



Performing the Diesel Induction & EGR Service:

- Start with air line disconnected from tool and ensure tool is depressurized.
- Fill canister with Wynn's Power Diesel™ Induction & EGR Cleaner (#ZW71032.)
- Ensure both valves are closed and set gauge pressure to 40-50 psi.
- Connect tool to appropriate adapters.

NOTE: *Refer to engine specific job aids. Service is performed at idle at normal operating temperatures. If engine begins to knock, close cleaner valve for 2 minutes then reopen.*

- **Service EGR Cooler:** Open air line (regulator side) first, then cleaner line.
- Apply 8 oz (250 ml) of cleaner, then close valve for 2 minutes. Repeat process until 50% of cleaner has been used.
- **Service Induction System:** Apply remaining cleaner (50%) in single step.
- Close valves when complete and set gauge pressure to 0 psi.
- Allow engine to idle for 10 minutes.
- Drive vehicle to clear remaining cleaner and carbon.

NOTE: *Manual regeneration of DPF may be required.*

